

BOSCH

LBB 3310 CCS 800 Control & Power Supply

Listen[®]

www.ListenTech.com



Specify Part Number

LBB 3310/00
LBB 3310/10

The Control and Power Supply Unit (CPSU) is the heart of a discussion system. Optionally the LBB 3310/10 version incorporates a digital acoustic feedback suppression, which allows any acoustic feedback (also known as "howling") to be automatically eliminated. With both versions users may manage the number of active microphones and determine the operating mode. Once set, there's no need for a central operator. External equipment can be connected to extend system possibilities. A built-in loudspeaker allows the conference to be monitored (to allow a stenographer, for example, to take notes on the conference).



LBB 3310/10 back view

Features

- Digital acoustic feedback suppression (only on LBB 3310/10 unit)
- Conference control without operator
- Four selectable microphone modes and a test mode
- Controls 150 contribution units
- Interfaces the system with external audio equipment
- Powers 50 contribution units
- Built-in listening facilities

Listen Technologies Corporation

8535 South 700 West, Suite A
Sandy, UT 84070-2515 U.S.A.
Phone: 1.801.233.8992 or 1.800.330.0891
Fax: 1.801.233.8995
Email: info@ListenTech.com

Don't miss a single sound.



Specifications

Interconnection	Input	Mains input connections. Line input and output for connecting a PA system or background music source.
	Output	Two trunk outputs for loop-through connection of contribution units. A maximum of 25 contribution units can be connected to each output. The maximum cable length is 328 ft. (100 m).
	Microphone Connection	Input with gain adjustment for connecting an external microphone.
	Recorder options	Input and output with gain control.
	Telephone Connection	Telephone coupler input and output for connecting a telephone line. The input signal is isolated from the output to prevent echoing.
	Audio Processing	Insertion connector (with by-pass switch) for connecting an audio processing unit.
	Digital Acoustic Feedback Suppression	DAFS button available on model LBB 3310/10 only
	Headphone Connection	One 3.5 mm stereo headphone socket.
Mounting	mounting type	Table top (portable or fixed mounting).
Physical	H x W x D	3.4 x 14.2 x 5.6 in. (84 x361 x 143 mm) includes 0.22 in. (5.5 mm) feet
	Weight	3.3 lb (1.5 kg)
	Color	cover: charcoal base: black

Photographs, CAD drawings, etc. available at www.ListenTech.com.

Contribution Equipment & Accessories**LBB 3330 Delegate Unit**

The LBB3330 delegate unit enables delegates to speak and listen to the proceedings via a loudspeaker or headphones. Available as LBB 3330/00 (shown) or LBB 3330/50 (longer mic stem).

**LBB 3331 Chairman Unit**

This stylish and ergonomically-designed chairman unit enables the user to function as chairman of a conference or meeting. Available as LBB 3331/00 (shown) or LBB 3331/50 (longer mic stem).

**LBB 3312/10 Transport & Storage Suitcase**

This transport and storage suitcase is for use in applications where CCS 800 Ultra contribution units will not be used in one fixed location.

**LBB 3316 Extension Cables**

Extension cable gives additional flexibility using the CCS 800. Cables are terminated at both ends. Available in 2 lengths, 16 ft. (5 m) (LBB 3316/05) and 32 ft. (10 m) (LBB 3316/10) are available to give additional system flexibility in larger application sites. Also available in 328 ft. (100 m) raw cable (LBB 3316/00) without connectors.